

EPDM - Commercial Grade - 60A

Specifications
March 2014

<u>Description:</u>	Ethylene Propylene Diene Monomer (EPDM) and SBR blended sheet is a black colored sheet rubber which provides very good resistance to weathering, ozone and UV exposure.
<u>Compound:</u>	10% Ethylene Propylene Diene Monomer (EPDM) Base, SBR
<u>Color:</u>	Black
<u>Weight:</u>	Approximate weight per square foot: 1/8" weighs 1-1/4 lbs.
<u>Durometer:</u>	60 Shore A, +/- 5
<u>Temperature Range:</u>	-40 F to 212 F
<u>Minimum Tensile:</u>	725 PSI or 5 MPA
<u>Finish:</u>	Smooth
<u>Minimum Elongation:</u>	300%
<u>Gauges:</u>	1/16", 3/32", 1/8", 3/16", 1/4", 3/8", 1/2" (custom gauges up to 2" thick are available upon request)
<u>Widths:</u>	36" (custom widths up to 78" are available upon request)
<u>Roll Length:</u>	25' or 50' depending on thickness.
<u>PSA:</u>	Pressure sensitive adhesive can be applied to this product upon request.
<u>Chemical Resistance:</u>	Good resistance to UV rays and ozone. Good resistance to Anti-freeze, Synthetic Detergents, Acetone, Boric acid, Ethanol, Formaldehyde, Mercury, Potassium Sulfate, Silver Nitrate, Steam (up to 212 Fahrenheit), Saccharin. For EPDM Blend's compatibility with your specific medium please consult a Rubber-Cal representative.
<u>Applications:</u>	Provides outstanding resistance to weathering, ozone and UV exposure. Gasket, bumper and general exterior applications.
<u>Flexibility:</u>	This medium durometer (55-65) sheet rubber offers good pliability and elasticity.
<u>Custom Cuts:</u>	In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.
<u>Availability:</u>	Popular gauges are generally in stock.



Rubber Cal

Specifications and/or prices are subject to change without prior notice.

© 2014 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.
620 West Warner Ave
Santa Ana, CA 92707
800-370-9152
www.rubbercal.com